



Project

Type

Catalog Number

SPECIFICATIONS

EXIT

HOUSING

- Acrylic panel
- Chevrons direction pre-selected

ELECTRICAL

- Requires 5fc of ambient light to activate phosphor
- No wiring necessary

ILLUMINATION

- Letters and chevrons have a 50' viewing distance
- Available in red, green, or back panels

MOUNTING

- Back mount
- Optional 1" stand-off barrels for back mount
- Wire suspension kit (up to 24" from ceiling); optional for 1-face, required for 2-face

CODE COMPLIANCE

- UL924 Listed for Wet Locations
- Meets NFPA101, NEC, OSHA, Local and State Codes
- Explosion Proof

WARRANTY

- 5 Year



**AC-PXE
Acrylic
Photoluminescent Exit**

ORDERING INFORMATION

MODEL#	Face #	Panel	Chevron Direction
AC-PXE	1	R (Red)	NA (No Arrow - 1/2 face)
	2	G (Green)	LA (Left Arrow - 1 face)
		B (Black)	RA (Right Arrow - 1 face)
			DA (Double Arrow - 1/2 face)
			LARA (Left Arrow/Right Arrow - 2 face)

ACCESSORIES (Order Separately, Ships on Side)

- WH - Wire-Hanger (up to 24" from ceiling - required for double faced signs)
- SB - Stand-Off Barrels (for 1" wall protrusion)

