

**SPECIFICATIONS**

**HARSH ENVIRONMENT**

**HOUSING**

- Heavy duty die-cast aluminum exit
- High abuse clear polycarbonate face plate
- Neoprene gasket
- Tamper-resistant screws standard
- Field selectable chevrons
- Can be ordered as single, double, or universal single/double

**ELECTRICAL**

- Dual 120/277V
- Charge rate/power "On" LED light and push-to-test switch for testing
- Standard Operating Temperature: 10°C - 40°C (50°F - 104°F)
- Heater Operating Temperature: -20°C (-4°F)

**ILLUMINATION**

- Ultra bright, energy efficient red or green LEDs

**BATTERY**

- Maintenance-free, rechargeable NiCad battery (EM models)
- Internal transfer switch automatically connects battery to LED board for 90-minute emergency illumination
- LVD (Low Voltage Disconnect) prevents battery from deep discharge
- Two-rate charger initiates battery charge to recharge in battery in 24 hours
- 120 Minute battery also available

**MOUNTING**

- Universal mounting canopy provided

**CODE COMPLIANCE**

- cSAus Listed for Wet Location
- Meets UL924, NFPA101, NEC, OSHA, Local and State Codes
- IP66 Rated
- ETL Sanitation Listed to NSF/ANSI standards
- CEC Title20 Approved
- BAA Compliant

**WARRANTY**

- 5 Year

**ORDERING INFORMATION**

MODEL#	# Faces	Letter	Housing
CAHAU	1	R (Red)	B (Black)
	2	G (Green)	W (White)
	3		

**Options (Factory Installed)**

EM	- NiCad Battery (Self Diagnostics standard)
EM2	- 120 Minute NiCad Battery
HTR	- Internal Heater (specify voltage)
IV	- Intermittent Visual Alarm (requires SD option)
FA	- Fire Alarm Interface
IRT	- Infrared Testing (specify voltage)
2C	- Dual Circuit (AC only)
SWXE	- Special Wording Panel (prefix to part number)

**Accessories (Order Separately, Ships on Side)**

IRT-R	- Controller for IRT (controller will operate multiple units)
SK12-W	- 12" Pendant Kit - White
SK12-B	- 12" Pendant Kit - Black
SK12-BA	- 12" Pendant Kit - Brushed Aluminum



**CAHA**  
Cast Aluminum  
High Abuse Exit

