

SPECIFICATIONS

EXITS

HOUSING

- Extruded aluminum housing
- White powdercoat finish standard, black and aluminum finishes also available
- Field selectable knockout chevron directional indicators

ELECTRICAL

- Dual 120/277V
- Charge rate/power "On" LED light and push-to-test switch for testing
- Standard Operating Temperature: 10°C - 40°C (50°F - 104°F)
- Less than 2W power consumption

ILLUMINATION

- Ultra bright, energy efficient red or green LEDs

BATTERY

- Maintenance-free, rechargeable NiCad battery (EM models)
- Internal transfer switch automatically connects battery to LED board for 90-minute emergency illumination
- LVD (Low Voltage Disconnect) prevents battery from deep discharge
- Two-rate charger initiates battery charge to recharge in battery in 48 hours
- 120 Minute battery also available

MOUNTING

- In-wall recess mount

CODE COMPLIANCE

- cSAus Listed for Indoor Locations
- Meets UL924, NFPA101, NEC, OSHA, Local and State Codes
- CEC Title20 Certified
- BAA Compliant

WARRANTY

- 5 Year



EAR Recessed Extruded Aluminum Exit

ORDERING INFORMATION

MODEL#	Face #	Letter	Housing
EAR	1	R (Red)	W (White)
		G (Green)	B (Black)
			A (Aluminum)

Options (Factory Installed)

EM	- NiCad Battery
EM2	- 120 Minute NiCad Battery
SD	- Self Diagnostics (requires EM)
2AC	- Dual Circuit (AC only)
TPS	- Tamper Proof Screws
SWXE	- Special Wording Panel (prefix to part number)

