

SPECIFICATIONS

HOUSING

- Extruded aluminum housing and canopy
- White finish standard, also available in brushed aluminum finishes
- Chevrons are field installable

ELECTRICAL

- Dual 120/277V
- Consumes 1.1W of power
- Charge rate/power "On" LED light and push-to-test switch for testing
- Standard Operating Temperature: 10°C 40°C (50°F 104°F)

ILLUMINATION

- Ultra bright, energy efficient LEDs
- Clear acrylic edgelit panel (single face), silver and white mylar acrylic panels (single and double faces)

BATTERY

- Maintenance-free, rechargeable NiCad battery
- Internal transfer switch automatically connects battery to LED board for 90-minute emergency illumination
- LVD (Low Voltage Disconnect) prevents battery from deep discharge
- Two-rate charger initiates battery charge to recharge in battery in 24 hours

MOUNTING

- Extruded aluminum canopy
- Exit can either be ceiling or wall mount

CODE COMPLIANCE

- cSAus Listed for Indoor Locations
- Meets UL924, NFPA101, NEC, OSHA, Local and State Codes
- CEC Title20 Certified
- BAA Compliant

WARRANTY

- 5 Year



EXITS

Project

Type

Catalog Number


EDGPO Oval Edgelit Exit

ORDERING INFORMATION

MODEL#	# Faces / Letter/ Panel	Housing
EDGPO	1RC (1 Face, Red Letters, Clear Panel)	A (Aluminum)
	2RS (2 Face, Red Letters, Mirror Panel)	W (White)
	2RW (2 Face, Red Letters, White Panel)	
	3RS (1 Face, Red Letters, Mirror Panel)	
	3RW (1 Face, Red Letters, White Panel)	
	1GC (1 Face, Green Letters, Clear Panel)	
	2GS (2 Face, Green Letters, Mirror Panel)	
	2GW (2 Face, Green Letters, White Panel)	
	3GS (1 Face, Green Letters, Mirror Panel)	
	3GW (1 Face, Green Letters, White Panel)	
Options (F	actory Installed)	
EM	- NiCad Battery	
SD	- Self Diagnostics (requires EM)	
SWXE	- Special Wording Panel (prefix to pa	rt number)

Accessories (Order Separately, ships on side)

SK12-* - 12" Pendant Kit *Specify <u>W</u>-White, <u>B</u>-Black, <u>BA</u>-Brushed Aluminum





10.29"