

SPECIFICATIONS

HARSH ENVIRONMENT

HOUSING

- Copper free cast aluminum alloy housing with 1/2" NPT conduit hubs
- Housing is fully gasketed in industrial gray finish
- Removable chevrons standard

ELECTRICAL

- 120/277VAC
- LED Indicator light for AC-ON
- Internal solid-state transfer switch
- Operating Temperature: up to 85°C (185°F)

BATTERY

- Maintenance-free NiCad battery (EM models) provides 180 minutes of emergency power
- Fully automatic solid-state charger initiates battery charging to recharge battery in 24 hours

ILLUMINATION

- Red or Green LEDs

MOUNTING

- Standard 1/2" NPT conduit hubs provided for alternate mounting options

CODE COMPLIANCE

- Suitable for Wet Location
- IP65 Rated
- BAA Approved
- Title20 Approved
- Class 1, Div 1, Groups C and D
- Class II, Div 1, Groups E, F, and G
- Class III

WARRANTY

- 5 Year



**HLEDG-DIV1
Explosion Proof
Hazardous Location
Edgelit**

CATALOG#	Description
HLEDG-DIV1-1RG-WP	Single Face, Red Letters, Gray Housing, Wall/Pendant Mount
HLEDG-DIV1-1GG-WP	Single Face, Green Letters, Gray Housing, Wall/Pendant Mount
HLEDG-DIV1-2RG-WP	Double Face, Red Letters, Gray Housing, Wall/Pendant Mount
HLEDG-DIV1-2GG-WP	Double Face, Green Letters, Gray Housing, Wall/Pendant Mount
HLEDG-DIV1-1RG-EB	Single Face, Red Letters, Gray Housing, End Mount
HLEDG-DIV1-1GG-EB	Single Face, Green Letters, Gray Housing, End Mount
HLEDG-DIV1-2RG-EB	Double Face, Red Letters, Gray Housing, End Mount
HLEDG-DIV1-2GG-EB	Double Face, Green Letters, Gray Housing, End Mount

Options (Factory Installed)

- EM - NiCad Battery
- SD - Self Diagnostics

