



Project

Type

Catalog Number

**SPECIFICATIONS**

**HARSH ENVIRONMENT**

**HOUSING**

- Stainless steel hardware
- A360 die-casting aluminum housing

**ELECTRICAL**

- AC100-277V
- Operating Temperature: -20°C - 60°C (-4 F° - 140 F°)

**ILLUMINATION**

- Tempered glass panel

**BATTERY**

- 3-hour emergency operation capability to maintain illumination during power outages
- 50,000 @ L<sub>70</sub>

**MOUNTING**

- Wall mount
- Mounting Arm available

**CODE COMPLIANCE**

- Class I, Div I, Groups C, D
- Class I, Div II, Groups A, B, C, D
- Class II, Div I, Groups E, F, G
- Class II, Div II, Groups F, G
- Class III
- IP66 Rated for Wet Locations
- UL1598A Marine Outside Type
- UL1598 Listed for Wet Locations
- UL844 Listed for Hazardous Locations
- BAA Compliance Available

**WARRANTY**

- 5 Year Warranty



**HLEX-F  
Hazardous Exit**

**ORDERING INFORMATION**

MODEL#	#Face	Face Color	Housing Color	Chevrons
HLEX-F	1	R (Red)	G (Gray)	Blank (No Arrows)
	2	G (Green)		LA (Left Arrow)
				RA (Right Arrow)
				DA (Double Arrow)
				RL (Right/Left Arrow - double face only)

**Options**

**BAA** - Buy American Compliant

**Accessories**

**HLEX-F-ARM** - Mounting Arm

