

SPECIFICATIONS

HARSH ENVIRONMENT

HOUSING

- NEMA4X fiberglass enclosure is corrosion and vandal resistant
- Housing is fully gasketed in an industrial gray finish

ELECTRICAL

- 120/277VAC
- LED Indicator light for AC-ON
- Internal solid-state transfer switch
- Operating Temperature: 10°C - 40°C (10°F - 104°F)

BATTERY

- Maintenance-free NiCad battery (EM models) provides 90 minutes of emergency power
- Fully automatic solid-state charger initiates battery charging to recharge battery in 48 hours

ILLUMINATION

- Weatherproof PAR36 Lamp Heads

MOUNTING

- Wall surface mount

CODE COMPLIANCE

- cSAus Listed for Wet Location
- BAA Approved
- Class 1, Div 2, Groups A, B, C and D

WARRANTY

- 5 Year

CATALOG#	Description
HLXC1*G-6V36	6V, 36W, Sealed Lead Acid Battery
HLXC1*G-6V42-NI	6V, 42W, NiCad Battery
HLXC1*G-6V54-NI	6V, 54W, NiCad Battery
HLXC1*G-6V60	6V, 60W, Sealed Lead Acid Battery
HLXC1*G-6V72	6V, 72W, Sealed Lead Acid Battery
HLXC1*G-6V90-NI	6V, 90W, NiCad Battery
HLXC1*G-6V100	6V, 100W, Sealed Lead Acid Battery
HLXC1*G-6V120	6V, 120W, Sealed Lead Acid Battery

HLXC*G-12V36	12V, 36W, Sealed Lead Acid Battery
HLXC*G-12V42-NI	12V, 42W, NiCad Battery
HLXC*G-12V60	12V, 60W, Sealed Lead Acid Battery
HLXC*G-12V90-NI	12V, 90W, NiCad Battery
HLXC*G-12V120	12V, 120W, Sealed Lead Acid Battery
HLXC*G-12V130-NI	12V, 130W, NiCad Battery
HLXC*G-12V140	12V, 140W, Sealed Lead Acid Battery

*Specify Letters: **R-Red**, **G-Green**

Options (Factory Installed)

SD	- Self Diagnostics)
TD	- Time Delay (specify voltage)
FA	- Fire Alarm Interface
VM	- Voltmeter
AM	- Ammeter
SM	- Side Mount Heads (top mount standard)
TPS	- Tamper Proof Screws
A1H	- Extra Lamp Head
A2H	- (2) Extra Lamp Heads
SWXE	- Special Wording Panel (prefix to part number)

Options (Factory Installed)

WG19	- Wireguard (12" x 9" x 9")
------	-----------------------------



HLXC
Hazardous Location
Combo

