

SPECIFICATIONS

STATE SPECIFIC

HOUSING

- Extruded Aluminum housing
- Available in aluminum, white, or black finished
- Can be ordered in single, double, or '3' face configurations
- Chevron indicators are field selectable

ELECTRICAL

- Dual 120/277V standard
- Operating Temperature: 0°C - 50°C (32°F - 122°F)

ILLUMINATION

- Red LEDs

BATTERY

- Maintenance free NiCad battery available
- Internal transfer switch automatically connects battery to lamp heads for 90-minute emergency illumination
- LVD (Low Voltage Disconnect) prevents battery from deep discharge
- Two-rate charger initiates battery charge to recharge in battery in 24 hours

MOUNTING

- Black aluminum canopy included for top, end, or back mount

CODE COMPLIANCE

- UL Listed for Damp Locations
- Meets UL924, NFPA101, NEC, OSHA, Local and State Codes
- CEC Title 20 Compliant

WARRANTY

- 5 Year

ORDERING INFORMATION

MODEL#	# Faces / Letter/ Panel	Housing
NYEDG	1RC (1 Face, Red Letters, Clear Panel)	A (Aluminum)
	2RS (2 Face, Red Letters, Mirror Panel)	W (White)
	2RW (2 Face, Red Letters, White Panel)s	B (Black)
	3RS (1 Face, Red Letters, Mirror Panel)	
	3RW (1 Face, Red Letters, White Panel)	

EX: NYEDG3RSW-EM-SD

OPTIONS (Factory Installed)

- EM - NiCad Battery
- SD - Self Diagnostics (requires EM)
- SV - 208/220/240V, 50/60Hz (AC only)

Accessories (Order Separately, Ships on Side)

- EDG-CANOPY-AL - Aluminum Canopy (black standard)
- EDG-CANOPY-WH - White Canopy (black standard)
- EDG-ENDCAP-AL - Aluminum Endcaps*

*Black and Aluminum models come with black, White models come with white



NYEDG
NYC Approved
Edgelit Exit

