



Project

Type

Catalog Number

SPECIFICATIONS

EXIT

HOUSING

- Rigid PVC Plastic
- Available unframed or framed
- Chevrons are field installable

ELECTRICAL

- Requires 5fc of ambient light to activate phosphor
- No wiring necessary

ILLUMINATION

- Letters and chevrons have a 50' viewing distance
- Available in red or green lettering

MOUNTING

- Unframed Exit: Flat wall installation (single); Requires clips - **CL** (double)
- Framed Exit: Flat wall accessories included (single); Requires bracket - **BR** (double)

CODE COMPLIANCE

- UL924 Listed for Wet Locations
- Meets NFPA101, NEC, OSHA, Local and State Codes
- Explosion Proof

WARRANTY

- 5 Year



PXEP
Photoluminescent Exit

ORDERING INFORMATION

MODEL#	Face #	Letters	Frame
PXEP	1	R (Red)	Blank (Unframed)
	2	G (Green)	SAF (Brushed Aluminum)



ACCESSORIES (Order Separately, Ships on Side)

CL	- Clips for Unframed Exits (required for ceiling mount double sided exits)
BR	- Bracket for Ceiling/End Mount (recommended for framed exits - not available for unframed)
BR10	- 10" Extended Ceiling Mount Bracket
BR19	- 19" Extended Ceiling Mount Bracket

