



Project

Type

Catalog Number

SPECIFICATIONS

ACCESSORIES

HOUSING

- Die-cast aluminum housing
- Powder coated aluminum canopy is fully gasketed
- Flex arm allows for repositioning

ELECTRICAL

- Available in 6V, 12V, 24V
- Operating Temperature: -30°C - 40°C (-22°F - 104°F)

ILLUMINATION

- Glass lens

MOUNTING

- Weatherproof canopy provided to fit most standard JBoxes for surface ceiling or wall applications

CODE COMPLIANCE

- cULus Listed for Wet Locations
- NEMA4X Rated
- NSF standard 2 Sanitation compliant
- BAA Compliant

WARRANTY

- 5 Year



**RHS
NEMA 4X Remotes**

ORDERING INFORMATION

Model#	Voltage	Lamp
RHS1	6V	LMR02 (2W LED, 12V)
RHS2	12V	LMR05 (5W LED, 6V/12V/24V)
	24V	LMR07 (7W LED, 6V/12V/24V)
		20WMR16 (20W MR16, 12V)
		35WMR16 (35W MR16, 12V)
		50WMR16 (50W MR16, 12V)

EX: RHS2-12V-LMR07

Options (Factory Installed)

- TL - Teflon Coated Lens

