

SPECIFICATIONS

EXITS

HOUSING

- Extruded aluminum recessed frame
- Painted extruded aluminum stencil
- 3/8" Polycarbonate vandal resistant cover standard
- Available in red, green, black, or brushed aluminum face plate
- Housing offered in white, black, bronze, or brushed aluminum finishes
- Universal chevrons

ELECTRICAL

- Requires no electricity or light source

ILLUMINATION

- 100ft visibility rating
- Light source consists of glass tubes which are internally coated with phosphor and filled with tritium gas (a natural hydrogen isotope)

BATTERY

- 10 or 20 year life span available
- Temperature Rating: -67°F - 176°F (-55°C - 80°C)

MOUNTING

- Recessed wall

CODE COMPLIANCE

- cULus Listed for Wet Locations
- Meets UL924, NFPA101, NEC, OSHA, Local and State Codes
- Explosion Proof

WARRANTY

- 5 Year



**RTEX
Recessed
Self Luminous Exit**

ORDERING INFORMATION

MODEL#	Face #	Letters	Housing	Service Life (yrs)
RTEX	1	R (Red)	W (White)	10
		G (Green)	B (Black)	20
		B (Black)	Z (Bronze)	
		Z (Bronze)	A (Aluminum)	

Options (Ships Installed)

SWXE - Special Wording (prefix to part number)

Accessories (Order Separately, Ships on Side)

WG-I-6 - Wireguard (20.0" x 17.0" x 12.0")

