



Project

Type

Catalog Number

SPECIFICATIONS

HARSH ENVIRONMENT

HOUSING

- Heavy duty die-cast aluminum exit
- High abuse clear polycarbonate face plate
- Neoprene gasket
- Tamper-resistant screws standard
- Field selectable chevrons
- Can be ordered as single, double, or universal single/double

ELECTRICAL

- Dual 120/277V
- Charge rate/power "On" LED light and push-to-test switch for testing
- Standard Operating Temperature: 10°C - 45°C (50°F - 113°F)
- Heater Operating Temperature: -20°C (-4°F)
- Consumes 2W or less power consumption

ILLUMINATION

- Ultra bright, energy efficient red or green LEDs

BATTERY

- Maintenance-free, rechargeable NiCad battery (EM models)
- Internal transfer switch automatically connects battery to LED board for 90-minute emergency illumination
- LVD (Low Voltage Disconnect) prevents battery from deep discharge
- Two-rate charger initiates battery charge to recharge in battery in 24 hours
- 120 Minute battery also available

MOUNTING

- Universal mounting canopy provided

CODE COMPLIANCE

- ETL Listed for Wet Locations
- Meets UL924, NFPA101, NEC, OSHA, Local and State Codes
- IP66 Rated
- ETL Sanitation Listed to NSF/ANSI standards
- BAA Compliant

WARRANTY

- 5 Year

ORDERING INFORMATION

MODEL#	# Faces	Letter	Housing/Face
SPCAHAU	1	R (Red)	B (Black)
	2	G (Green)	W (White)
	3		

Options (Factory Installed)

EM	- NiCad Battery
EM2	- 120 Minute NiCad Battery
SD	- Self Diagnostics (EM models only)
HTR	- Internal Heater (EM only, specify voltage)
IV	- Intermittent Visual Alarm (requires SD option)
FA	- Fire Alarm Interface (requires SD) specify type - open/closed dry contact
2C	- Dual Circuit (AC only)
SWXE	- Special Wording Panel (prefix to part number)

Accessories (Order Separately, Ships on Side)

SK12-W	- 12" Pendant Kit - White
SK12-B	- 12" Pendant Kit - Black
SK12-BA	- 12" Pendant Kit - Brushed Aluminum



SPCAHA
Slim Cast Aluminum
High Abuse Exit

