

SPECIFICATIONS

STATE SPECIFIC

HOUSING

- Durable 20 gauge steel
- Field adjustable chevrons standard
- White housing standard
- Brushed aluminum also available
- Universal mounting pattern and key hole slots are stamped into housing

ELECTRICAL

- Dual voltage 120/277VAC
- Rated for use indoor locations
- Solid state charger and transfer
- Brownout protection

ILLUMINATION

- Acrylic face plate in clear, white, or mirrored
- 2W power consumption

BATTERY

- Maintenance free, NiCad battery provides a minimum of 90 minutes in emergency mode
- 120 minute battery optional
- Recharging time is 24 hours
- Maximum battery temperature is 45°C

CODE COMPLIANCE

- cCSAus Listed for Indoor Locations
- Meets UL Requirements

WARRANTY

- 5 year warranty

ORDERING INFORMATION

MODEL#	Face/Letter/Panel	Housing	Mounting
SWXECT-EDGU	1RC (Single Face, Red on Clear)	W (White)	RC (Recessed Ceiling)
	2RS (Double Face, Red on Silver)		RW (Recessed Wall)
	2RW (Double Face, Red on White)		SC (Surface Ceiling)
	3RS (Single Face, Red on Silver)		SW (Surface Wall)
	3RW (Single Face, Red on White)		SE (Surface End)
	1GC (Single Face, Green on Clear)		
	2GS (Double Face, Green on Silver)		
	2GW (Double Face, Green on White)		
	3GS (Single Face, Green on Silver)		
	3GW (Single Face, Green on White)		

OPTIONS (Factory Installed)

BA	- Brushed Aluminum Housing (replaces W in part number)
EM	- NiCad Battery (90 minute)
EM120	- NiCad Battery (120 minute)
INV	- Inverted Face

ACCESSORIES (Order Separately, Ships on Side)


SK12-* - 12" Stem Kit (other lengths available)

*Specify **W-White**; **B-Black**; **BA-Brushed Aluminum**




SWXECT-EDGU Connecticut Approved Edgelit


Recessed Ceiling




Surface Ceiling/End



Recessed Wall



Surface Wall



Model	A	B	C	D	E	F	G
RC	19.50"	11.25"	17.50"	5.00"	7.25"	4.00"	4.00"
WR	19.50"	10.00"	17.50"	5.50"	8.00"	4.00"	4.00"
SC	19.50"	11.00"	17.50"	4.25"	7.25"	4.00"	4.00"
WS	19.50"	10.00"	17.50"	5.50"	8.00"	4.00"	4.00"
ES	19.50"	11.25"	17.50"	4.25"	7.25"	4.00"	4.00"